



北川鉄工所 スクロールチャック用

SBS



爪形状



取付ボルト穴寸法

| インチ | 穴径(mm) |
|-----|--------|
| 6 | 13.5 |
| 7 | 17 |
| 9 | 19 |
| 10 | 19 |
| 12 | 19 |

単位：mm

| 生爪型式 | 希望小売価格 (1set3個入/円・税別) | A | B | C | D | E | F | G | H | I | J | K | 爪形状 | 材質 | 質量 (kg) | |
|------|--------------------------|--------|-----|------|-------|------|-----|-------|-------|-------|-------|-------|-----|------|------------|------|
| SBS | 6 | H36 | 77 | 26 | 36 | 7.94 | 3 | 3.5 | 38.1 | M8 | 41 | 12.68 | - | A | S50C | 1.70 |
| | | 60 | | | 2.50 | | | | | | | | | | | |
| | 6B | H32 | 73 | 26 | 32 | 7.94 | 3 | 3.5 | 38.1 | M8 | 41 | 12.68 | 9 | B | S45C | 1.50 |
| | | H48 | | | 48 | | | | | | | | | | | 1.80 |
| | | H73 | | | 73 | | | | | | | | | | | 2.60 |
| | | H38 | | | 38 | | | | | | | | | | | 2.30 |
| | 7 | H60 | 92 | 28 | 60 | 7.94 | 3 | 3.5 | 44.45 | M10 | 48 | 12.68 | - | A | S50C | 3.40 |
| | | H90 | | | 90 | | | | | | | | | | | 4.00 |
| | | H32 | | | 6,700 | | | | | | | | | | | 89 |
| | H48 | 10,800 | 48 | 2.70 | | | | | | | | | | | | |
| | H73 | 14,600 | 73 | 3.50 | | | | | | | | | | | | |
| | H100 | 23,800 | 100 | 4.90 | | | | | | | | | | | | |
| | H120 | 27,800 | 120 | 6.50 | | | | | | | | | | | | |
| | H150 | 34,900 | 150 | 7.10 | | | | | | | | | | | | |
| | 9 | H45 | 100 | 32 | 45 | 12.7 | 3 | 3.5 | 53.98 | M12 | 55 | 19.03 | - | A | S50C | 3.10 |
| | | H60 | | | 60 | | | | | | | | | | | 4.00 |
| | | H90 | | | 90 | | | | | | | | | | | 5.40 |
| | 9B | H32 | 103 | 31 | 32 | 12.7 | 3 | 3.5 | 53.98 | M12 | 58 | 19.03 | 13 | B | S45C | 1.78 |
| | | H48 | | | 48 | | | | | | | | | | | 3.12 |
| | | H63 | | | 63 | | | | | | | | | | | 4.16 |
| H80 | | 80 | | | 5.20 | | | | | | | | | | | |
| H100 | | 100 | | | 5.60 | | | | | | | | | | | |
| H120 | | 120 | | | 9.20 | | | | | | | | | | | |
| 10 | H48 | 110 | 35 | 48 | 12.7 | 3 | 3.5 | 53.98 | M12 | 60 | 19.03 | - | A | S50C | 4.40 | |
| | H60 | | | 60 | | | | | | | | | | | 5.50 | |
| | H90 | | | 90 | | | | | | | | | | | 8.30 | |
| 10B | H50 | 110 | 35 | 50 | 12.7 | 3 | 3.5 | 53.98 | M12 | 60 | 19.03 | 13 | B | S50C | 2.95 | |
| | H60 | | | 60 | | | | | | | | | | | 3.60 | |
| | H75 | | | 75 | | | | | | | | | | | 4.20 | |
| 12 | H51 | 125 | 40 | 51 | 12.7 | 3 | 3.5 | 63.5 | M12 | 67.5 | 19.03 | - | A | S50C | 5.20 | |
| | H90 | | | 90 | | | | | | | | | | | 9.60 | |
| 12B | H54 | 125 | 40 | 54 | 12.7 | 3 | 3.5 | 63.5 | M12 | 67.25 | 19.03 | 13 | B | S50C | 5.24 | |
| | H70 | | | 70 | | | | | | | | | | | 9.30 | |
| | H90 | | | 90 | | | | | | | | | | | 9.50 | |
| | H120 | | | 120 | | | | | | | | | | | 11.70 | |

※生爪兼用表は120ページを参照ください。

生爪

北川鉄工所 スクロールチャック用

SBS長爪



単位：mm



■ 材質：S50C

| 生爪型式 | 希望小売価格 (1set3個入/円・税別) | A | B | C | D | E | F | G | H | I | J | 爪形状 | 質量 (kg) |
|-------------|--------------------------|-----|----|----|------|---|-----|-------|-----|-------|-------|-----|------------|
| 7 H48 L150 | 27,800 | 150 | 31 | 48 | 7.94 | 3 | 3.5 | 44.45 | M10 | 110.8 | 12.68 | A | 3.80 |
| 9 H48 L150 | 30,600 | 150 | 31 | 48 | 12.7 | 3 | 3.5 | 53.98 | M12 | 103 | 19.03 | A | 4.14 |
| 10 | 北川生爪「SBS-9」をご使用ください | | | | | | | | | | | | |
| 12 H48 L180 | 36,200 | 180 | 40 | 48 | 12.7 | 3 | 3.5 | 63.5 | M12 | 122.3 | 19.03 | A | 6.80 |

※生爪兼用表120ページを参照ください。